

ISO/IEC 19752 Yield Test Report



Toner Cartridge TN-3280 **with DR-3200 for *HL-5340D / HL-5350DN / HL-5370DW** **DCP-8085DN / MFC-8880DN / MFC-8890DW**

* These models use the same engine.

Declaration of yield:

Toner cartridge yield : 8,000pages Approx. cartridge yield in accordance with ISO/IEC 19752.

For questions concerning testing contact

Average 8,698
Standard Deviation 360
90% Lower Confidence 8,475

Brother Industries, Ltd.
1-1-1, Kawagishi, Mizuho-ku,
Nagoya, 467-8562, JAPAN

Date Tested:	From 13-Jan-2009 to 15-Jan-2009
Number of Cartridges used in testing	9
Number of Cartridges used in calculations	9
Type of Cartridge	Separate type (Toner and Drum)
Shake Procedure Used?	No
Print mode	Continuous
Number of engines used in testing	3
Media Used/Paper Size	Xerox 4200 DP Paper /Letter
Paper feed orientation	Short edge feed
Computer Model	HITACHI FLORA 270W
Driver Version	Version 1.0.1 for Windows 2000/XP
Operating System	Windows XP SP2
Application Software	Acrobat Reader 8.1.2
Test Page Version	c034911_ISO_IEC_19752_2004(E)_Test_Page.pdf
Power (off/on) everyday?	Yes

Cartridge testing data

Toner Cartridge	Drum Cartridge	*1 Printer	*2 Temperature (C) Avg	*2 Humidity (%) Avg	Cartridge Yield	Cart Used in Calculation
A9JG000018A	A9J5018417G	M8J000030G	23	50	8,816	Y
A9JG000014A	A9J5018417G	M8J000030G	23	50	8,686	Y
A9JG000028A	A9J5018417G	M8J000030G	23	50	8,646	Y
A9JG000015A	A9J5018410G	M8J000044G	23	50	8,700	Y
A9JG000031A	A9J5018410G	M8J000044G	23	50	8,209	Y
A9JG000013A	A9J5018410G	M8J000044G	23	50	8,630	Y
A9JG000039A	A9J5018418G	M8J000050G	23	50	9,486	Y
A9JG000029A	A9J5018418G	M8J000050G	23	50	8,318	Y
A9JG000020A	A9J5018418G	M8J000050G	23	50	8,794	Y

*1 The tested printer is HL-5340D

* 2 Temperature and Humidity are controlled by chamber room.